## **Product specification**

Product name	Lifter CSYQ1000A					
ltem	Name	Symbol	SI		CGS	
Shape	Radian	R	255	mm	25.5	cm
	Lengh	L	268	mm	26.8	cm
	Width	W	179	mm	17.9	cm
	Height	Н	164	mm	16.4	cm
	Direction of magnetization	М	Assiale			
	Surface treatment	-	-	μm		
Measuring point	Surface flux density	В	-	mT	-	G
	Attractive force	F	1000	kgf	1000000	gf
	Magnetic flux density on load point	Bd	-	mT	-	G
	Total flux	Dia o	-	Wb	-	Mx
	Permeance coefficient	Pc	-	Pc	-	
	Operationg temperature range	Tw	-	deg C	-	deg F
	Operationg temperature range	Tw	-	deg C	-	deg F
Material characteristics	Material grade	Lifter	Alnico5			
	Remanence	Br	-	mT	-	kG
	Coericive forces	Hcb	-	kA/m	-	kOe
	Intrisic coercivity	Hcj	-	kA/m	-	kOe
	Maximum energy product	BH	-	kJ/m3	-	MGOe
	Temperature	Br	-	%/deg C	-	%/deg F
	coefficient	Hcj	-	%/deg C	-	%/deg F
	Max. operating temperature	Tw	-	deg C	-	deg F
	Curie temperature	Тс	-	deg C	-	deg F
	Density	Р	-	kg/m3	-	
	Weight	Net	55.5	kg	55500	g

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.