## **Product specification**

Product name	Magnetic Bar Dia16mmX300mm						
Item	Name	Symbol	SI		CGS		
Shape	Diameter	D	16	mm	1.6	cm	
	Diameter	d	10	mm	1	cm	
	Lengh	L	300	mm	30	cm	
	Screw	М	6	mm	0.6	cm	
	Direction of magnetization	М	Assiale				
	Surface treatment	Polish	-	μm			
Measuring point	Surface flux density	В	1000	mT	10000	G	
	Attractive force	F	-	kgf	-	gf	
	Magnetic flux density on load point	Bd	-	mT	-	G	
	Total flux	Dia o	-	Wb	-	Mx	
	Permeance coefficient	Pc	-	Pc	-		
	Operationg temperature range	Tw	100	deg C	212	deg F	
	Operationg temperature range	Tw	-	deg C	-	deg F	
Material characteristics	Material grade	Magnetic Bar	316				
	Remanence	Br	-	mT	-	kG	
	Coericive forces	Hcb	-	kA/m	-	kOe	
	Intrisic coercivity	Hcj	-	kA/m	-	kOe	
	Maximum energy product	BH	-	kJ/m3	-	MGOe	
	Temperature	Br	-	%/deg C	-	%/deg F	
	coefficient	Нсј	-	%/deg C	-	%/deg F	
	Max. operating temperature	Tw	-	deg C	-	deg F	
	Curie temperature	Тс	-	deg C	-	deg F	
	Density	Р	-	kg/m3	-		
	Weight	Net	0.452	kg	452	g	
Remark		REACH RoHS Directive					

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.